

PalmTop™ Monitor specifications

Optional comprehensive graphics monitor for the EnVe™ ventilator

Monitored and trended values

Ppeak	PEEP
Vte	Pmean
Rate	Ve
I:E	FiO₂
PIFR	PEFR
Vleak	O₂ inlet
Spon rate	Spon Vte
Pulse	SpO₂
SBT time	f/Vt
SBT f	C stat
Pplat	Auto PEEP
dPAW	Pexp

Patient and ventilator data

Waveforms	Pressure, flow, volume and pleth
Loops	Flow/volume, volume/pressure
Trending	24 hour trend of all patient monitors



Storage conditions

Temperature	-20° C to 60° C (-4° F to 140° F)
Humidity	10% to 95% relative, non-condensing

Operating conditions

Temperature	5° C to 40° C (41° F to 104° F)
Humidity	15% to 95% relative, non-condensing

Packaging


Dimensions	11.25" h x 12" w x 2" d (28.58 cm x 30.48 cm x 5.08 cm)
Dimensions with mounting arm	17.25" h x 12" w x 2" d (43.82 cm x 30.48 cm x 5.08 cm)
Weight	≤ 6.5 lbs (2.95 kg)




Ventilator settings			
PEEP	Volume	O ₂ flush duration	SBT duration
VeiCalc	Inspiration time	O ₂ percent	SBT FiO ₂
Bias flow	Flow sensitivity	Inspiration pause	SBT PSV
Rise time	Pressure sensitivity	Flow Cycle	SBT PEEP
Leak comp	Pressure support	Breath type	
PSV Rise	Pressure control	Breath mode	
O ₂ flush level	PSV Tmax	Breath rate	

Ventilator alarms			
Apnea interval	High pressure	High FiO ₂	High min volume
High tidal volume	Low pressure	Low FiO ₂	Low min volume
Low tidal volume	High PEEP	PEEP delay	High breath rate
High pressure delay	Low PEEP	LPP alarm	Low breath rate
SBT high f/Vt	SBT high f	V/BR delay	High pulse
SBT low f/Vt	SBT low f	High SpO ₂	Low pulse
Safety valve data pressure		Low SpO ₂	Inop

 **WARNING:** U.S. Federal Law restricts this device to sale by or on the order of a physician.

 CareFusion
 22745 Savi Ranch Parkway
 Yorba Linda, CA 92887
 800.231.2466 toll-free
 714.283.2228 tel
 714.283.8493 fax

 CareFusion Germany 234 GmbH
 Leibnizstrasse 7
 97204 Hoechberg
 Germany
 +49 931 4972-0 tel
 +49 931 4972-423 fax

carefusion.com

