

# EnVe™ docking station specifications

Critical care ventilation

## Ventilator docking interface

<b>Ventilator communication port</b>	The PalmTop™ Ventilator docking station will establish communication with a ventilator within five seconds, when docked	
	VOXP protocol	
<b>Nurse call port</b>	<b>Mechanical</b>	4-position RJ type female connector
	<b>Electrical</b>	Closed contact resistance ≤ 1 ohm, electrically isolated  Open contact resistance ≥ 1 m.ohm, electrically isolated

## Power

<b>External AC power connection</b>	<b>Input voltage range</b>	100 to 240 VAC, 50 to 60Hz
	<b>Input power connector</b>	IEC 320 (with connector clamp)
<b>PalmTop™ Monitor DC power connection</b>	<b>Output voltage</b>	14 to 16 VDC
	<b>Output current</b>	up to 1.4 A




## Physical dimensions (width x height x depth)


<b>Size</b>	5 5/8" w x 7 1/4" h x 12" d (14.2 cm x 18.4 cm x 30.4 cm)
<b>Weight</b>	5 lbs (2.3 kg)

## Environmental

<b>Temperature</b>	<b>Storage</b>	-20° C to 60° C (-4° F to 140° F)
	<b>Operating</b>	5° C to 40° C (41° F to 104° F)
<b>Humidity</b>	<b>Storage</b>	Up to 95% relative, non-condensing
	<b>Operating</b>	15% to 95% relative, non-condensing
<b>Altitude</b>	<b>Storage</b>	50,000 feet maximum above sea level
	<b>Operating</b>	68 to 106 kPa

 **WARNING:** U.S. Federal Law restricts this device to sale by or on the order of a physician.

 CareFusion  
22745 Savi Ranch Parkway  
Yorba Linda, CA 92887  
800.231.2466 toll-free  
714.283.2228 tel  
714.283.8493 fax

 CareFusion Germany 234 GmbH  
Leibnizstrasse 7  
97204 Hoechberg  
Germany  
+49 931 4972-0 tel  
+49 931 4972-423 fax

[carefusion.com](http://carefusion.com)

© 2010 CareFusion Corporation or one of its subsidiaries. All rights reserved. EnVe and PalmTop are trademarks of CareFusion Corporation or one of its subsidiaries. RC1705 (0810/4000) L3316 Rev. A

