

Vivo 50

The Vivo* 50 Life-Support Ventilator combines high quality technology with robust, premium Scandinavian design to provide excellent patient treatment in home and portable in various environments.

Vivo 50 includes a full range of settings, including target volume which leads to a strong combination of performance and flexibility.

Vivo 50 offers the possibility to pre-set up to three ventilation profiles. Thanks to the user-friendly configuration of pressure and volume regulated modes, the treatment can be personalised to the patient's needs. High flexibility of operation is provided by the multiple types of circuits for both invasive and non-invasive ventilation.

Vivo 50 is easy to learn, easy to operate and easy to explain. A full-colour screen and distinct buttons provide easy access to all functions. The menu structure is simple and effective. An **i**-button explains functions and alarms with a click.

Accessories enhance the Vivo 50 ventilators ease of use, performance, durability and cost-effective service for both the patient, clinical staff and homecare providers.



Intended Use

The Vivo 50 ventilator (with or without the iOxy and CO₂ sensor) is intended to provide continuous or intermittent ventilatory support for the care of individuals who require mechanical ventilation. Specifically, the ventilator is applicable for pediatric through adult patients weighing at least 10 kg (22 lbs).

The Vivo 50 with the iOxy is intended to measure functional oxygen saturation of arterial hemoglobin (% SpO₂) and pulse rate.

The Vivo 50 with the CO₂ sensor is intended to measure CO₂ in the inspiratory and expiratory gas.

The device is intended to be used in home, institution, hospitals and portable applications such as wheelchairs and gurneys.

It may be used for both invasive and non-invasive ventilation. Vivo 50 is not intended to be used as a transport ventilator and critical care ventilator.

- Full monitoring allows view of waveforms, numerical data and trend monitoring.
- Possibility to connect a patient start/stop remote, remote alarm and nurse call system.
- Easy direct access to menus on the user-friendly front panel.
- Freedom of operation thanks to a 4 hour internal battery and the option of an additional 8 hours from the click-on battery.
- The SpO₂ and CO₂ sensors give the unit high-end monitoring capabilities with on-screen values and alarms.
- The **i**-button makes information on alarms, settings and troubleshooting available.

Technical Specifications

Settings/Performance	
Ventilation Modes	<ul style="list-style-type: none"> • PSV • PCV • PCV(A) • VCV • CPAP • PSV(TgV) • PCV(TgV) • PCV(A+TgV) • VCV(A)
Device Modes	<ul style="list-style-type: none"> • Home • Clinical
Inspiratory Pressure	4 to 50 cmH ₂ O
PEEP	2 cmH ₂ O (leakage circuit), 0 cmH ₂ O (circuit with active exhalation valve) to 30 cmH ₂ O Pressure - 2 cmH ₂ O or Min Pressure -2 cmH ₂ O
Breath Rate (PCV, VCV)	4 to 40 bpm
Inspiratory Time	0.3 to 5 s
Backup Inspiratory Time	0.3 to 5 s (PSV)
Rise Time	1 to 9 (PSV & PCV) 50 - 90 %, Off (VCV)
Inspiratory Trigger	1 to 9 (PSV, PCV & VCV) Off (PCV & VCV)
Expiratory Trigger	1 to 9 (PSV)
Minimum Inspiratory Time	Off, 0.3 to 3 s
Maximum Inspiratory Time	0.3 to 3 s, Off
Backup Rate (PSV)	4 to 40 bpm
Target Volume	100 to 2500 ml
Maximum Pressure	50 cmH ₂ O
Minimum Pressure	4 cmH ₂ O to 50 cmH ₂ O
Tidal Volume	100 to 2500 ml
Flow Pattern	Square, decelerating
CPAP	4 to 20 cmH ₂ O

Power Supplies		Monitoring	
Mains supply	100 to 240 V AC	Displayed data<	Ppeak, PEEP, Pmean, Leakage, MV, Vt, % in TgV, Total Rate, Spont Rate, % Spont, SpO ₂ , Pulse Rate, I:E, Inspiratory Time, Rise Time, EtCO ₂ , InspCO ₂
External battery	24 V DC	Waveforms	Pressure, Flow, Volume
Click-on battery	8 hours	Trends over 1, 6, 24 and 48h	Ppeak, PEEP, Total Rate, Spont Rate, Vt, Leakage, SpO ₂ , EtCO ₂
Internal battery	4 hours		

Main Alarms		Dimensions	
High Pressure, Low Pressure, High PEEP, Low PEEP, High Vt, Low Vt, High MV, Low MV, High Breath Rate, Low Breath Rate, Apnea, Disconnection, Rebreathing, High SpO ₂ , Low SpO ₂ , High EtCO ₂ , Low EtCO ₂ , High InspCO ₂ , High Pulse Rate, Low Pulse Rate, Low Last Power Source		W x H x D	13,5 x 4,9 x 10,4 inches without click-on battery (13,5 x 4,9 x 11,2 inches with click-on battery)
		Weight	11 lbs without click-on battery (13,2 lbs with click-on battery)
		Noise level (at 10 cmH ₂ O constant pressure)	Less than 30 dB(A)

*Vivo by Breas is a trademark of Breas Medical AB

© 2014 Breas Medical - All rights reserved.
Breas Medical reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation.
Contact your Breas representative for the most current information.
Breas and the Breas logo are trademarks of Breas Medical AB.

BREAS

Breas Medical AB · Företagsvägen 1 · SE-435 33 Mölnlycke · Sweden
Phone +46 31 86 88 00 · Fax +46 31 86 88 10 · www.breas.com